

**WEST****End of Result Set**

Generate Collection

Print

L1: Entry 1 of 1

File: JPAB

May 21, 1988

PUB-NO: JP363116907A

DOCUMENT-IDENTIFIER: JP 63116907 A

TITLE: PNEUMATIC TIRE MOUNTING METHOD ON TWO-WHEELED VEHICLE

PUBN-DATE: May 21, 1988

## INVENTOR-INFORMATION:

NAME

COUNTRY

KOBAYASHI, TOSHIAKI

## ASSIGNEE-INFORMATION:

NAME

COUNTRY

BRIDGESTONE CORP

APPL-NO: JP61261851

APPL-DATE: November 5, 1986

US-CL-CURRENT: 152/209.8

INT-CL (IPC): B60C 11/06; B60C 11/08

## ABSTRACT:

PURPOSE: To restrain the tire in the title having roof shaped grooves in the transverse direction on the tread from the unsymmetrical wear so as to improve the grip characteristic, by mounting a front tire so that the broadened ends of the roof shaped grooves will come in contact with the ground first and mounting a rear tire so that the tapering ends of the roof shaped grooves will come in contact with the ground first.

CONSTITUTION: A front wheel tire 1a is to be mounted on a wheel in the direction as instructed on the tire so that the broadened side 3A of a roof shaped transverse grooves will come in contact with the ground first when the tire is in rotating direction (a). Conversely, a rear wheel tire 1b is to be mounted on a wheel so that the tapering end side 3B of the roof shaped grooves will come in contact with the ground first when the tire is in the rotating direction (a). The unsymmetrical wear can be restrained so that the grip characteristic can be improved by this constitution.

COPYRIGHT: (C)1988, JPO&amp;Japio